

**Fiberglass Fabric with PTFE Resin Coating Sleeve with VELCRO® Brand  
Hook & Loop Closure**  
**550°F / 287°C: Continuous Rating – Higher Temperature for Shorter Periods**  
**Scuff-Sleeve™ VC**



- Specialty protection for hoses, wire and cables.
- Sleeve with Velcro for easy retrofit.
- Sleeve is made from fiberglass base fabric impregnated with a PTFE resin coating. Excellent chemical resistance. Temperature range - 60°F to +550°F. Excellent UV protection. Not for use near open flame or welding.
- Used for food processing robot cables, lines and hoses.
- Washdown resistant
- Removeable for machine cleaning

**Fiberglass Fabric with PTFE Resin Coating Sleeve with VELCRO® Brand Closure (Continued)****550°F / 287°C: Continuous Rating – Higher Temperature for Shorter Periods****Scuff-Sleeve™ VC**

Sold in 50 foot increments up to 150 feet continuous rolls. Available in standard sizes; larger or custom sizes can be easily fabricated if required. Helps to organize and bundle hoses and cables.

<b>Scuff-Sleeve™ VC: PTFE Impregnated Fiberglass Fabric Specialty Protection Sleeve with VELCRO® Brand Hook &amp; Loop Closure</b>				
<b>Part Number</b>	<b>Size inch / mm / -dash</b>			<b>Price per Foot</b>
				<b>FG/PTFE resin</b>
S-FG-PTFE-VCL-M025-16 *	1.00	25	-16	£ 12.03
S-FG-PTFE-VCL-M051-32	2.00	51	-32	£ 15.60
S-FG-PTFE-VCL-M064-40	2.50	64	-40	£ 16.76
S-FG-PTFE-VCL-M070-44	2.75	70	-44	£ 18.28
S-FG-PTFE-VCL-M076-48	3.00	76	-48	£ 19.55
S-FG-PTFE-VCL-M083-52	3.25	83	-52	£ 20.36
S-FG-PTFE-VCL-M089-56	3.50	89	-56	£ 21.47
S-FG-PTFE-VCL-M102-64	4.00	102	-64	£ 22.36
S-FG-PTFE-VCL-M127-80	5.00	127	-80	£ 23.84
S-FG-PTFE-VCL-M152-96	6.00	152	-96	£ 24.91
S-FG-PTFE-VCL-M178-112	7.00	165	-104	£ 31.40
S-FG-PTFE-VCL-M203-128	8.00	203	-128	£ 32.37

**Custom sizes available**

Width of the Velcro is 1.5" except part numbers indicated with (\*) which is .75".