

Tacky Cloth™ Luting & Groove Packing

550°F / 287°C: Tuff-Flex™ High Temperature Heat Resistant, Wire Inserted



- Luting & groove packing.
- Formed square: available rectangular or round.
- Standard 25 and 50 foot lengths.
- Add +25% to the price for non standard lengths.

550°F / 287°C continuous rating, excellent sealing properties as a gasket material

Tuff-Flex™ High Temperature Luting & Groove Packing - Square			
Part Number	Size in / mm	Price per Foot Regular / Graphite Coated	
T-FG-TC-LGP-M010-06-X	.375 / 10	£ 5.70	£ 11.20
T-FG-TC-LGP-M013-08-X	.500 / 13	£ 6.43	£ 11.93
T-FG-TC-LGP-M016-10-X	.625 / 16	£ 9.37	£ 14.87
T-FG-TC-LGP-M019-12-X	.750 / 19	£ 9.90	£ 15.40
T-FG-TC-LGP-M022-14-X	.875 / 22	£ 12.47	£ 17.97
T-FG-TC-LGP-M025-16-X	1.00 / 25	£ 17.50	£ 22.97
T-FG-TC-LGP-M029-18-X	1.125 / 29	£ 19.57	£ 23.40
T-FG-TC-LGP-M032-20-X	1.250 / 32	£ 31.93	£ 37.43
T-FG-TC-LGP-M038-24-X	1.500 / 38	£ 32.67	£ 38.16

For the “X” value specify either “R” for Regular, or “GC” for Graphite Coated

Standard Rolls of 25 and 50 feet. Other lengths add +25% to price.

Curing: It is recommended that this material be cured in situ. This material must be heated to a minimum of 300°F within 60 minutes, then it must sit at 300°F or higher for 90 minutes for the rubber to fully cure.

Do not overtorque the material during this curing time or the rubber will be squeezed off of the base material.

If the material is not fully cured, the rubber will drip from the material causing voids. After curing the material can be exposed to a lower operational temperature.