

**L-3 Communications Tape, Electrical,
 Silicone Self-Fusing, Non-Reinforced**
500°F / 260°C: Meeting A-A-59163 Class 1, Type I Specifications
Also meets MIL-I-46852 & Many Other OEM Specifications
Self Binding Self-Fusing Tape - High Temperature, Heat & Flame Resistant



- Self-bonds / self fuses / self amalgamating. No sticky residue or adhesive when removed. Starts fusing within minutes, fully bonded within hours. Excellent cold weather performance. Makes an excellent compression tape.
- Excellent for sealing ends of firesleeve: prevents sleeve from absorbing contamination and wicking liquids. Excellent for wrapping electrical & mechanical connections and splices. Makes clean and neat installations of cables, wires and hoses. Makes an instant separation bumper and provides vibration dampening.
- Meets A-A-59163 specifications. Certification available.
- Standard roll length is 36 feet / 12 Yards / 10.9 Metres; other lengths available. Colour is Black.
- Add £6.00 for individual roll CofC. Lot/Batch CofC £10.00 per order line item.
- Cage Code L8347.

L-3 Communications Tape, Electrical, Silicone Self-Fusing, Non-Reinforced
Meets A-A-59163 Specifications: Class 1, Type I

| Part Number | Tape Width Inches / mm | Thickness inches / mm | Type / Profile | Single Roll Price Per Roll |
|-------------------|---------------------------|--------------------------|-----------------|-------------------------------|
| T-SR-40014362-000 | 1/2 / 13 | 0.020 / 0.5 | I / Rectangular | £ 29.37 |
| T-SR-40014362-001 | 3/4 / 19 | 0.020 / 0.5 | I / Rectangular | £ 31.96 |
| T-SR-40014362-002 | 1 / 25 | 0.020 / 0.5 | I / Rectangular | £ 34.71 |
| T-SR-40014362-003 | 1.25 / 32 | 0.020 / 0.5 | I / Rectangular | £ 41.77 |